

WIN VISION Air

Pixel pitch	mm	9.375	
Brightness	cd / m ²	5,000	2,200
LED type	-	3-in-1 SMD	
Viewing angle	degree : H	110° (min 50% brightness)	
	degree : V	110° (min 50% brightness)	
Transparency	-	30%	
Size (W x H x D)	mm / tile	600mm x 1,200mm x 65 mm	
Weight	tile / sqm	7.7 kg / 10.7 Kg	6.9 Kg / 9.6 Kg
IP Rating	-	65 (Front)	
Pixel density	pixel / tile	8,192	
	pixel / sqm	11,377	
Use Temperature	Operating (°C)	-10°C ~ 40°C / 14°F ~ 104°F	
	Storage (°C)	-20°C ~ 50°C / -22°F ~ 122°F	
Lifetime	hrs	50,000 (@50 % brightness)	
Operation power	VAC, Hz	100 - 240V , 50/60 Hz	
Power consumption (max./average)	W / tile	360(max) / 144(average)	190 (max) / 76 (average)
	W / sqm	500(max) / 200(average)	264 (max) / 106 (average)
Max. Power Connection	-	8 tile	16 tile
Max. Data Connection	-	16 tile	
Color Process	bit / color	16	
Max. Hanging	-	8 tile (9.6M)	
Serviceability	-	Front	
Certifications	-	ETL, CE, TUV, FCC	

